



Ashlar

Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product	Interpret	Color	Black	Collection	Shifted	States	Collection	Backing	GlasBac™
Product Specifications									
Product Number		1405802500							
Product Construction		Tufted Pattern Loop							
Yarn System		100% Recycled Content Nylon							
Yarn Manufacturer		Aquafil							
Dye Method		100% Solution Dyed							
Soil/Stain Protection		Protekt ² ®							
Preservative Protection		Intersept®							
More Product Specifications									
		Imperial			Metric				
Tufted Yarn Weight		19 oz/yd ²			644 g/m ²				
Machine Gauge		1/10 in			39.4 ends/10cm				
Pile Height		0.15 in			3.8 mm				
Pile Thickness		0.121 in			3.1 mm				
Stitches		10 /in			39.37 ends/10cm				
Pile Density		5,653 oz/yd ³			209,612 g/m ³				
Size		19.69 in x 19.69 in			50cm x 50cm				
Performance Specifications									
Flooring Radiant Panel		(ASTM E-648) Passes							
Smoke Density		(ASTM E-662) ≤ 450							
Flammability		Passes Methenamine Pill Test (DOC-FF1-70)							
Lightfastness		(AATCC 16 - E) ≥ 4.0 @ 60 AFU's							
Static		(AATCC - 134) < 3.0 KV							
Dimensional Stability		(ASTM F2199) Passes							
Traffic Classification		Heavy							
Fiber Modification Ratio		1.9 to 2.2							
Preservative Efficacy		(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition							
Health + Environmental Specifications									
Embodied Carbon (Cradle to Gate)		4.7 Kg CO ₂ /M ²							
Total Recycled Content		68.61 %							
Recycled Content (Pre Consumer)		58.52 %							
Recycled Content (Post Consumer)		10.09 %							
Indoor Air Quality		Green Label Plus #GLP0820 CDPH 01350							
Material Composition		Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.							
Disclosure of Environmental Impacts		Environmental Product Declaration							
Disclosure of Product Ingredients		Health Product Declaration							
Environmental Certifications		NSF/ANSI 140 Gold GreenCircle Certified Recyclable							
LEED v4		Contributes to multiple IEQ and MR credits							
End of Life		Carpet to Carpet Recycling through ReEntry®							
Technical Information									
Installation		Interface Installation Guidelines							
Maintenance		Recommended Interface Maintenance Guidelines							
Reclamation		Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)							
Warranty		15 Year Standard Carpet Warranty							
Installation Method		Monolithic Ashlar							
Manufacturing Location		ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States							